



## High-performance and cost-effective filter bags for *absolute* applications

Eaton's LOFCLEAR 500 filter bags are suitable for a wide range of applications such as the filtration of oils and slurries, dilute oil removal, process fluids with heavy contamination and many more.

LOFCLEAR 500 filter bags feature fully-welded, multi-pleated construction for high efficiency and long service life. This range has a pleated pre-filter and a complex arrangement of final filter layers, allowing the removal of difficult-to-filter gels and deformable particles with a high dirt-holding capacity. The webbed cover layer virtually eliminates any downstream fiber migration.

### Features and benefits

- Fully-welded construction with patented Santoprene™ SENTINEL® seal ring provides 100% bypass-free filtration
- High dirt-holding capacity of more than 2.2 lbs (1,000 g)
- Pleated pre-filter provides a very large filter area (approx. 32 ft<sup>2</sup> (3 m<sup>2</sup>))
- Material is free from silicone and crater-forming substances<sup>1</sup>
- Eaton strongly recommends the use of an insertion tool that facilitates the insertion of the filter bag into the bag filter housing and ensures the correct alignment of the filter bag inside the restrainer basket

### Filter specifications

**Material**  
Melt-blown polypropylene

**Cover layer**  
Spunbond polypropylene

**Seal ring**  
Welded Santoprene  
SENTINEL seal ring

**Retention ratings<sup>2</sup>**  
2.6, 6, 13, 32 µm  
@ > 99% efficiency

### Dimensions/Parameters

**Size**  
02: Ø 7 x 31" L (180 x 795 mm)

**Filter area**  
02: 5.2 ft<sup>2</sup> (0.48 m<sup>2</sup>)  
(plus approx. 32 ft<sup>2</sup> (3 m<sup>2</sup>) pleated pre-filter)

**Max. operating temperature**  
194 °F (90 °C)

**Max. differential pressure**  
36.2 psi (2.5 bar)

**Recommended change-out pressure for disposal<sup>3</sup>**  
11.6 – 21.7 psi (0.8 – 1.5 bar)

**Max. flow rates<sup>4</sup>**  
02: 53 GPM (12 m<sup>3</sup>/h)




Powering Business Worldwide

# LOFCLEAR 500 Filter Bag Range

## Filter removal efficiency

Models	Particle sizes (µm) at common removal efficiencies (%)				Δp psi (bar) size 02 @ 44 GPM (10 m³/h)	Max. operating temperature °F (°C)
	> 60%	> 90%	> 95%	> 99%		
522	0.5	1	1.5	2.6	1.9 (0.13)	194 (90)
525	1	2	3.5	6	1.2 (0.08)	194 (90)
527	2	5	9	13	0.1 (0.008)	194 (90)
529	10	20	23	32	< 0.1 (0.005)	194 (90)

## Ordering information



A pleated pre-filter offers a very large filter area (approx. 32 ft² (3 m²)), to retain gels and solids before they reach subsequent filter layers.

<sup>1</sup> Based on an accepted paint compatibility test (see document QUC-STA-10).

<sup>2</sup> Reference values based on single pass tests in ambient lab conditions with ISO test dust in water at 44 GPM (10 m³/h)/size 02.

<sup>3</sup> Depending on the respective application requirements.

<sup>4</sup> For liquids with a dynamic viscosity of 1 mPa·s @ 68 °F (20 °C).

Santoprene™ is a registered trademark of Exxon Mobil Corporation.

**North America**  
44 Apple Street  
Tinton Falls, NJ 07724  
Toll Free: 800 656-3344  
(North America only)  
Tel: +1 732 212-4700

**Europe/Africa/Middle East**  
Auf der Heide 2  
53947 Nettersheim, Germany  
Tel: +49 2486 809-0

**Internormen** Product Line  
Friedensstraße 41  
68804 Altlußheim, Germany  
Tel: +49 6205 2094-0

**Begerow** Product Line  
An den Nahewiesen 24  
55450 Langenlonsheim, Germany  
Tel: +49 6704 204-0

**China**  
No. 3, Lane 280,  
Linhong Road  
Changning District, 200335  
Shanghai, P.R. China  
Tel: +86 21 5200-0099

**Singapore**  
4 Loyang Lane #04-01/02  
Singapore 508914  
Tel: +65 6825-1668

**Brazil**  
Av. Julia Gaioli, 474 – Bonsucesso  
07251-500 – Guarulhos, Brazil  
Tel: +55 11 2465-8822

For more information, please  
email us at [filtration@eaton.com](mailto:filtration@eaton.com)  
or visit [www.eaton.com/filtration](http://www.eaton.com/filtration)

© 2014 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

US  
EF-FTB-05c  
08-2014