



Pleated filter bags manufactured from extended-life needle felt

Eaton's MAX-LOAD extended-life pleated filter bags are suitable for a wide range of applications, such as water treatment, chemicals, paints and varnishes, petrochemicals, metal cleaning and many more.

MAX-LOAD pleated filter bags are manufactured from nominal rated polypropylene or polyester extended-life needle felt. The exceptional construction increases the filter bags dirt-holding capacity and lifetime by up to ten times more than standard needle felt filter bags.

Features and benefits

- Increases dirt-holding capacity by up to a factor of ten compared to a similar size standard needle felt filter bag¹ [1.5 lbs (700 g) per filter bag, size 02]
- Lowers maintenance costs due to a longer lifetime
- Fits into all Eaton standard size 01 and size 02 restrainer baskets
- Special surface treatment virtually eliminates fiber migration

- Material is free from silicone and crater-forming substances²
- Patented SENTINEL® seal ring provides 100% bypass-free filtration
- The pressure-activated SENTINEL seal ring provides a flexible, chemically resistant seal which adapts to any bag filter housing

Filter specifications

Materials

Extended-life needle felt polypropylene or polyester

Seal rings

Polypropylene or polyester SENTINEL seal ring

Retention ratings

1, 5, 10, 25, 50 µm

Dimensions/Parameters

Sizes

01: Ø 7 x 14" L (180 x 345 mm)
02: Ø 7 x 29" L (180 x 730 mm)

Filter area

01: 8.6 ft² (0.8 m²)
02: 17.2 ft² (1.6 m²)

Max. operating temperature

Polypropylene: 194 °F (90 °C)
Polyester: 275 °F (135 °C)

Max. differential pressure

36.2 psi (2.5 bar)

Recommended change-out pressure for disposal³

11.6 – 21.7 psi (0.8 – 1.5 bar)


Max. flow rates⁴

01: 44 GPM (10 m³/h)
02: 88 GPM (20 m³/h)




Powering Business Worldwide

MAX-LOAD Filter Bag Range



Extended-life needle felt in comparison to standard needle felt


- Finer fibers
- Greater porosity
- Thicker media



Surface of a MAX-LOAD pleated filter bag

- Glazed finish binds loose fibers on the surface
- Full flow through surface channels

Ordering information



¹ Based on internal lab tests.

² Based on an accepted paint compatibility test (see document QUC-STA-10).

³ Depending on the respective application requirements.

⁴ For liquids with a dynamic viscosity of 1 mPa·s @ 68 °F (20 °C).

North America

44 Apple Street
 Tinton Falls, NJ 07724
 Toll Free: 800 656-3344
 (North America only)
 Tel: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
 53947 Nettersheim, Germany
 Tel: +49 2486 809-0

Intermornen Product Line

Friedensstraße 41
 68804 Altlußheim, Germany
 Tel: +49 6205 2094-0

Begerow Product Line

An den Nahwiesen 24
 55450 Langenlonsheim, Germany
 Tel: +49 6704 204-0

China

No. 3, Lane 280,
 Linhong Road
 Changning District, 200335
 Shanghai, P.R. China
 Tel: +86 21 5200-0099

Singapore

4 Loyang Lane #04-01/02
 Singapore 508914
 Tel: +65 6825-1668

Brazil

Av. Julia Gaioli, 474 – Bonsucesso
 07251-500 – Guarulhos, Brazil
 Tel: +55 11 2465-8822

For more information, please
 email us at filtration@eaton.com
 or visit www.eaton.com/filtration

© 2015 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

US
 EF-FTB-18
 10-2015